KA® Industrial Degreaser

The perfect choice for cleaning and degreasing a variety of surfaces and items including air filters, concrete flooring, conveyors, exhaust hoods, walls, metal equipment, and machine parts.

- High alkaline butyl-based formulation.
- Authorized for use under NSF Category A1.
- Phosphate free, non-combustible.

Technical Specifications

Appearance	Clear
Dilution Rate	1:128 - 1:1
Color	Red
Scent	Mild Solvent
Non Volatile Matter	12.50 - 13.50%
pH @ 25 deg. C	12.50 - 13.50





NSF

Safety

Availability

See material safety data sheet and product for safety information, handling and proper use.

HMIS (Concentrate/RTU)

Flammability = 0

Health = 3

Reactivity = 0

HIL0013706	4 - 1 Gallon Containers
HIL0013707	1 - 5 Gallon Bag-In-Box
HIL0013709	1 - 55 Gallon Drum
HIL0013711	1 - 275 Gallon Tote
HIL0013728	1 - 30 Gallon Drum

Certifications, Registrations & Notes

NSF Registered NSF A1, Nonfood Compound, Cleaning Products, General Cleaner



Directions

Formulated to remove the toughest grease, oil, tar, and grime. Apply diluted KA INDUSTRIAL DEGREASER with a sprayer, brush, mop, or sponge, depending on the surface to be cleaned. May also be applied with pressure equipment and automatic scrubbers. Excellent for cleaning and degreasing air filters, concrete flooring, exhaust hoods, conveyors, walls, metal equipment and parts, and basically any hard surface not damaged by water. Rinse with hot or cold water. Phosphate free, non- combustible.

LIGHT SOIL CONDITIONS: Dilute 1:128 (1 oz./gal. of water).

AVERAGE SOIL CONDITIONS: Dilute 1:32 (4 oz./gal. of water).

HEAVY SOIL CONDITIONS: Dilute 1:10 (12 oz./gal. of water).

DEGREASING: Dilute 1:1 to 1:4 (32 oz./gal. of water).

NOTICE: DO NOT USE ON GLASS.

