

# Super Strip

Hillyard Super Strip will easily remove the toughest buildup on the floor. Even floors that have been repeatedly burnished and hardened with multiple coats of finish are rapidly stripped. Super Strip is formulated to provide powerful stripping action no matter what the condition of the floor.

- Powerful stripping for any floor condition.
- Works fast.
- Super concentrated.

## Technical Specifications

Appearance	Clear
Dilution Rate	1:10 - 1:5
Color	Colorless to Light Amber
Scent	Mild Solvent
Non Volatile Matter	14.00 - 19.00%
pH @ 25 deg. C	13.0 - 14.0

## HMIS (Concentrate/RTU)

Flammability = 0      Health = 3      Reactivity = 0



## Safety

See material safety data sheet and product for safety information, handling and proper use.

## Availability

HIL0015206	4 - 1 Gallon Containers
HIL0015207	1 - 5 Gallon Bag-In-Box
HIL0015209	1 - 55 Gallon Drum

## Directions

Do not use on asphalt tile, linoleum, synthetic sports floors, rubber, painted, or varnished surfaces. **(DO NOT USE ON WOOD.)**

**PRETEST:** Pretest in small area for color bleeding or discoloration or softening that may occur on linoleum, rubber, or asphalt tile on an inconspicuous area. Do not continue use of product if any bleeding or softening is observed.

**APPLICATION:** 1. Dilute accordingly with cool to warm water. For normal stripping dilute 13 oz./gallon (1:10) of water. For aggressive stripping dilute 26 oz./gallon of water (1:5). 2. Apply solution liberally with a mop. 3. Allow 4-5 minutes contact time. Be sure to keep surface wet at all times. Agitate with a low-speed rotary machine or automatic scrubber. 4. Pick up solution using a wet vacuum or automatic scrubber. 5. Allow floor to dry thoroughly. Rinse with NUTRA-RINSE solution for best results.

**NOTICE:** Floor may become slippery when stripper is present. Pick up solution immediately with wet vac or mop. Damp mop rinse. Apply polish after floor is clean and dry. Stripper vapors or liquid may cause discoloration on uncured, light colored painted surfaces. **DO NOT USE ON GLASS.**