

# Assurance®

Highly concentrated, multipurpose cleaner removes a wide variety of dirt, grime and grease. Use for cleaning any hard surface not damaged by water. Do not use on glass. Can be applied with a mop, sponge, brush, foam gun, or pressure washer. Ideal for use in automatic scrubbers at an economical dilution rate of one ounce per gallon of water. Phosphate free. Contains no soap, free alkali, or ammonia.

- Concentrated for economical cost-in-use.
- No rinsing saves time.
- Pleasant citrus fragrance.

## Technical Specifications

Appearance	Clear
Dilution Rate	1:256 - 1:32
Color	Orange
Scent	Lemon
Non Volatile Matter	12.00 - 13.00%
pH @ 25 deg. C	12.50 - 13.50

## HMIS (Concentrate/RTU)

Flammability = 0      Health = 3      Reactivity = 0

## Certifications, Registrations & Notes

Kosher Certification™

This product is certified Kosher™ and parve (contains no animal or dairy products) by Whole Kosher Services and may be used all year round excluding Passover.



## Safety

See material safety data sheet and product for safety information, handling and proper use.

## Availability

HIL0015306	4 - 1 Gallon Containers
HIL0015307	1 - 5 Gallon Bag-In-Box
HIL0015309	1 - 55 Gallon Drum
HIL0015328	1 - 30 Gallon Drum

## Directions

For use on resilient tile, concrete, paver brick, quarry tile, terrazzo, marble, tables, walls, and machinery. Can be applied with a mop, an automatic scrubber, sponge, brush, foam gun, or pressure washer.

**LIGHT CLEANING:** Apply at dilution rate of 1:256 (.5 oz. per gallon of water).

**NORMAL CLEANING:** Use a dilution rate of 1:128 (1 oz. per gallon of water).

**EXTRA HEAVY CLEANING:** Use a dilution rate of 1:32 (4 oz. per gallon of water). Use dilutions can be adjusted to the amount of soil and type of soil load.

**SCRUBBING AND RECOATING FLOORS:** Use a dilution rate of 1:32 (4 oz. per gallon of water) and use 175 rpm rotary machine or autoscrubber to prepare floor prior to recoating with floor polish.

**FOR AUTOMATIC SCRUBBER:** Use a dilution rate of 1:128 (1 oz. per gallon of water) for routine floor cleaning.

**FOR DEGREASING:** For removal of fats, oils, and grease from floors and walls in kitchens and food processing areas (clay tile, concrete, terrazzo floors, and walls). Remove heavy soil from surfaces and equipment manually or with high pressure sprayer and hot water. Dilute 1:32 with hot water (4 oz. per gallon of water) and apply by mopping, spraying, or wiping. Scrub surface with floor machine, sponge, brush, or cloth. Pick up solution and rinse with hot water.

**NOTICE:** DO NOT USE ON GLASS.