

# Super Grease Buster®

Removes fats, oils and cooking grease from all washable surfaces in kitchens and food processing areas. Ideal for cleaning ceramic tile, concrete, terrazzo, tables, equipment, walls, etc. Not for use on glass. Approved for use on all surfaces in all departments of federally- inspected egg, meat, poultry and rabbit plants. NSF Category A-1. Contains no butyl. Phosphate-free, nonflammable and biodegradable.

- Non-butyl and phosphate free.
- Nonflammable and biodegradable.
- Concentrated for economical cost-in-use.

## Technical Specifications

Appearance	Clear
Dilution Rate	1:128 - 1:2
Color	Colorless
Scent	Odorless
Non Volatile Matter	4.00 - 5.00%
pH @ 25 deg. C	12.50 - 13.50

## HMIS (Concentrate/RTU)

Flammability = 0      Health = 3      Reactivity = 0

## Certifications, Registrations & Notes

NSF Registered

NSF A1, Nonfood Compound, Cleaning Products, General Cleaner

Kosher Certification™

This product is certified Kosher™ and parve (contains no animal or dairy products) by Whole Kosher Services and may used all year round excluding Passover.



## Safety

See material safety data sheet and product for safety information, handling and proper use.

## Availability

HIL0015606	4 - 1 Gallon Containers
HIL0015607	1 - 5 Gallon Pail
HIL0015609	1 - 55 Gallon Drum

## Directions

Removal of fats, oils, and cooking greases from all washable surfaces in kitchens and food processing areas (clay tile, concrete, terrazzo floors, walls, tables, etc.): Remove heavy soil from surfaces and equipment manually or with high pressure sprayer and hot water. Dilute 1:20 (6 oz./gal. of hot water) and apply by mopping, spraying, or wiping. Scrub surface with floor machine, sponge, brush, or cloth. Pick up solution and rinse with hot water.

Removal of oil, grease, and carbon from automobile motors, parts, and garage equipment: Dilute 1:2 (64 oz./gal. of water). Spray entire surface thoroughly. Let stand for one minute, then flush with water.

Removal of soap scum, film, and other debris on locker rooms and shower stalls: Dilute 1:4 (32 oz./gal. of water).

General cleaning of concrete, terrazzo, and ceramic tile floors: Dilute 1:128 (1 oz./gal. of water). Rinse with water, mop dry. Dilute 1:20 (6 oz./gal. of water) for use in automatic scrubber; remove soiled cleaning solution and rinse thoroughly with clean water.

Dilute 1:128 (1 oz./gal.) for use on latex wall paint. Test cleaning solution on an inconspicuous area for effect on paint before using. DO NOT PROCEED if adverse effects occur.

### **DO NOT USE ON GLASS.**

**NOTICE:** In Federally inspected meat and poultry plants, follow all usage with a thorough potable water rinse.