

Defoamer II

A concentrated, stable white emulsion, specially formulated to eliminate foam in recovery tanks of carpet cleaning equipment, automatic floor scrubbers, and wet pickup vacuums. It acts quickly to help prevent foam from being pulled into the electrical vacuum motor, where moisture can cause rust and other damage.

- Prevents foam buildup.
- No moisture reaches the electrical vacuum motor.
- Works in hot or cold water.

Technical Specifications

Appearance	Milky, viscous liquid
Dilution Rate	1:20 - 1:256
Color	White
Scent	Non-objectionable
Non Volatile Matter	1.20 - 1.70%
pH @ 25 deg. C	5.50 - 7.50



Safety

See material safety data sheet and product for safety information, handling and proper use.

HMIS (Concentrate/RTU)

Flammability = 0 Health = 0 Reactivity = 0

Availability

HIL0018304	12 - 1 Quart Bottles
HIL0018306	4 - 1 Gallon Containers
HIL0018309	1 - 55 Gallon Drum

Directions

For new vacuums or vacuums that have not been treated with HILLYARD DEFOAMER II, pour 6 ounces of concentrated DEFOAMER II into a quart of water and pick up through the vacuum system. This step treats the total vacuum system, not just the recovery tank.

After the initial treatment, determine the size of the vacuum recovery tank and pour in .5 to 1 ounce of DEFOAMER II per gallon of recovery tank capacity.

If excessive foam does begin to form in the vacuum tank during operation, an additional amount of DEFOAMER II may be added to control the suds. (Do not exceed 6 ounces per gallon of tank capacity.)