

HV-Pro

An industrial vehicle wash specifically formulated for hand vehicle washing systems. HV-Pro removes most exhaust deposits, road film, and bug residue from painted vehicle surfaces, cleans aluminum siding, painted wood, and painted metal surfaces. HV-Pro rinses residue-free and water will bead up for that just waxed look. For use with hot or cold water, HV-Pro is heat stable to 180° Fahrenheit, and contains no solvents, free acids or phosphates.

- Great foaming characteristics.
- Effective in hot or cold water.
- Can also be used in pressure washers.

Technical Specifications

Appearance	Clear
Dilution Rate	1:20 - 1:128
Color	Green
Scent	Non-objectionable
Non Volatile Matter	6.75 - 7.75%
pH @ 25 deg. C	8.00 - 9.50

HMIS (Concentrate/RTU)

Flammability = 0 Health = 2 Reactivity = 0

Directions

DIRECTIONS: Dilute product according to label directions. Allow solution to penetrate soil for 5 minutes. Rinse thoroughly with clean water. Can use with brush cleaning. Light cleaning: Dilute 1oz. HV-Pro into 1 gallon of water. Medium Cleaning: Dilute 3oz. HV-Pro into 1 gallon of water. Heavy Cleaning: Dilute 6oz. HV-Pro into 1 gallon of water



Safety

See material safety data sheet and product for safety information, handling and proper use.

Availability

HIL0045306 4 - 1 Gallon Containers
HIL0045309 1 - 55 Gallon Drum