

# CV-Pro

An industrial vehicle wash specifically formulated for use with high pressure cleaning equipment. CV Pro removes most exhaust deposits, road film, and bug residue from painted vehicle surfaces, cleans aluminum siding, painted wood, and painted metal surfaces. CV Pro rinses residue- free and water will bead up for that "just waxed look". For use with hot or cold water, CV-Pro is heat stable to 180° Fahrenheit, and contains no solvents, free acids or phosphates.

- Rinses residue free.
- Effective in hot or cold water.
- Contains no solvents, free acids or phosphates.

## Technical Specifications

Appearance	Clear
Dilution Rate	1:20 - 1:64
Color	Red
Scent	Non-Objectionable
Non Volatile Matter	4.50 - 6.50%
pH @ 25 deg. C	11.50 - 12.50

## HMIS (Concentrate/RTU)

Flammability = 0      Health = 2      Reactivity = 0

## Directions

Dilute product according to label directions. Allow solution to penetrate soil for 5 minutes. Rinse thoroughly with clean water. Can use with brush cleaning.

**Light cleaning:** Dilute 1:64 (2 oz. per gallon of water).

**Medium Cleaning:** Dilute 1:32 (4 oz. per gallon of water).

**Heavy Cleaning:** Dilute 1:20 (6 oz. per gallon of water).



## Safety

See material safety data sheet and product for safety information, handling and proper use.

## Availability

HIL0047907	1 - 5 Gallon Pail
HIL0047909	1 - 55 Gallon Drum
HIL0047911	1 - 275 Gallon Tote