

# O.S.R. Oil Spot Remover

Oil Spot Remover is designed to absorb and lift stains from concrete without scrubbing. Simply pour on spot, allow the product to dry and absorb the spot. Then, brush away. Can be used on concrete surfaces indoors or outdoors. Commonly used on concrete driveways, garages, and walkways.

- Remove oil spots without scrubbing
- Extracts oil embedded deep into concrete
- Dries to a powder for easy removal

## Technical Specifications

Appearance	Opaque
Dilution Rate	RTU
Color	White
Scent	Citrus
Non Volatile Matter	15.00 - 17.00%
pH @ 25 deg. C	9.00 - 11.00



## Safety

See material safety data sheet and product for safety information, handling and proper use.

## HMIS (Concentrate/RTU)

Flammability = 0

Health = 2

Reactivity = 0

## Availability

HIL0049122

6 - 1/2 Gallon Containers

## Directions

**DIRECTIONS:** Prior to applying O.S.R. remove excess oil and grease from concrete and let dry. Pour O.S.R. onto oily/greasy spot on concrete. Allow product to set on soil for 2-4 hours. Sweep or vacuum from the concrete, then bag and dispose of waste. (For heavier oil spots allow product to dwell overnight.) For best results, allow O.S.R. to dry to a powder prior to removal. Some oil spots may require a second application due to the deeper oil leeching to the surface. After O.S.R. has dried to a powder and has been removed, a white residue may be present. The residue will go away on its own but if you desire to remove this residue immediately, you may scrub with Hillyard SM-1® and a green scrub pad.