

H.R. 2000®

A high gloss restorer formulated to deliver a deep gloss while it protects your base coat and keeps traffic lanes, heel marks, and scuffing to a minimum. H.R. 2000 resists powdering caused by the heat and friction generated with ultra-high speed equipment, plus its durable formula helps extend time between recoating. H.R. 2000 contains no heavy metals (a potential issue for wastewater treatment facilities) making H.R. 2000 an excellent choice to complement a zinc-free floor maintenance program.

- Resists powdering from the heat and friction of burnishing.
- Helps extend time between recoating.
- Contains no heavy metals, a great compliment to a zinc-free program.

Technical Specifications

Appearance	Milky Emulsion
Dilution Rate	1:42 - 1:1
Color	White Emulsion
Scent	Lemon
Non Volatile Matter	7.00 - 8.00%
pH @ 25 deg. C	7.50 - 8.50

HMIS (Concentrate/RTU)

Flammability = 0 Health = 0 Reactivity = 0

Certifications, Registrations & Notes

UL Approved

Classified by Underwriters Laboratories, Inc. as to slip resistance. (186S).



Safety

See material safety data sheet and product for safety information, handling and proper use.

Availability

HIL0053804 12 - 1 Quart Bottles
HIL0053806 4 - 1 Gallon Containers

Directions

PREPARATION: For optimum results, establish a good base coat with HILLYARD ONE PLUS, NORTH STAR, TOP SHAPE, EXPLORER or ENDEAVOR. Dust mop daily using HILLYARD SUPER HIL-TONE or HIL-MIST Damp mop or autoscrub as needed with HILLYARD ASSURANCE or TOP CLEAN before using H.R. 2000.

APPLICATION: MOPPING METHOD FOR 1000 TO 3000+ RPM MACHINES - Dilute one part H.R. 2000 to four parts water and apply thin film. When dry, burnish with high speed machine equipped with high speed pad. For battery or electric machines, use HILLYARD 100-D neutral polythermal pads. For propane machines, use HILLYARD beige polythermal pads.

SPRAY METHOD FOR 175 -1500 RPM MACHINES - Dilute one part H.R. 2000 to one part water and apply with a pump-up type sprayer or spray bottle. Spray light mist to small area and immediately buff. For 175 RPM machines, use a red pad. For 1000-1500 RPM machines use a HILLYARD beige polythermal pad.

AUTO-BURNISH METHOD FOR AUTOMATIC SCRUBBERS - Dilute 3 ounces of H.R. 2000 to each gallon of water. Autoscrub floor area to be treated. Let dry and burnish to a high gloss using floor machines of 1000 RPM speed or higher equipped with Hillyard beige polythermal floor pad. DUST MOP FLOOR IMMEDIATELY AFTER FINAL BUFFING OF H.R. 2000 USING SUPER HIL-TONE OR HIL-MIST TREATED DUST MOP.

NOTICE: Keep container closed when not in use. Do not pour unused product back into container. Best results are obtained with adequate ventilation and floor temperatures above 60°F (16°C). Do not use on buffable waxes.