

# Green Select® Stripper

Green Seal certified. Formulated to be, non-toxic, phosphate free, biodegradable, and non-flammable, and it contains no dye or fragrance. Formulated to strip Hillyard One Plus® and EP-22, Hillyard Green Select high solids, zinc-free floor polishes. It can be used to strip a variety of other polishes as well. When used as directed, it is safe to apply to asphalt, vinyl, vinyl composition, and even linoleum. It does an outstanding job of wetting, penetrating, and emulsifying polish.

- Non-toxic, phosphate free, biodegradable, non-flammable.
- No dye or fragrance and effective in cold water.
- Green Seal certified.

## Technical Specifications

Appearance	Clear
Dilution Rate	1:4 - 1:8
Color	Colorless
Scent	Mild Solvent
Non Volatile Matter	11.00-14.00%
pH @ 25 deg. C	11.00 - 12.00

## HMIS (Concentrate/RTU)

Flammability = 0      Health = 2      Reactivity = 0

## Certifications, Registrations & Notes

Green Seal™ Certified

This product meets Green Seal™ Standard GS-40 based on effective performance and protective limits on VOCs and human & environmental toxicity. GreenSeal.org.



## Safety

See material safety data sheet and product for safety information, handling and proper use.

## Availability

HIL0096406	4 - 1 Gallon Containers
HIL0096407	1 - 5 Gallon Bag-In-Box
HIL0096409	1 - 55 Gallon Drum

## Directions

Add 16 ounces of GREEN SELECT STRIPPER to each gallon of cold water (1:8 dilution) for light to medium buildup and 32 ounces (1:4 dilution) for heavy buildup. Apply a liberal amount to the floor with a clean mop, keeping floor uniformly wet. Let stand 10 minutes, then scrub with floor machine using a stripping pad to break up softened film. (Do not use abrasive pads on tile containing asbestos.) Work small areas, keeping floor wet at all times. Pick up the stripping solution with a wet vac, mop, or autoscrubber. Rinse thoroughly with Nutra-Rinse solution. Pick up solution and damp mop with clean water. Repeat if polish is not removed. Mix solution carefully. Some types of asphalt tile and linoleum may be discolored by stripper. To correct, scrub with a solution of SUPER SHINE-ALL and cold water (3 oz./gal.). Repeat if necessary. Rinse thoroughly before recoating with floor polish.

**PRETEST:** Test on an inconspicuous area using 1:1 dilution. Allow to stand on floor 10 minutes. Wipe off with towel, rinse, and examine floor for bleeding or softening. Do not continue use if any deleterious effect is observed.

**NOTICE:** Floor may become slippery when stripper is present. Stripper vapors or liquid may cause discoloration on uncured, light colored painted surfaces. To conserve energy always use cold tap water