

Baseboard Stripper

This heavy-duty, foaming product is designed to remove excess floor finish where floor machines cannot reach. The thick, penetrating foam clings to vertical surfaces like baseboards for easy removal of wax build-up. Wax build-up is quickly emulsified by chemical action for easy removal, leaving a wax-free surface.

- Removes heavy wax build-up in hard to reach areas.
- Clinging Foam Adheres to Surfaces.
- Easy Rinsing.

Technical Specifications

Dilution Rate	RTU
Color	Pale beige
Scent	Pine
pH @ 25 deg. C	11.50 - 12.50



Safety

See material safety data sheet and product for safety information, handling and proper use.

Availability

HIL0113355

12 - 19 oz. Cans

Certifications, Registrations & Notes

NSF Registered

NSF C1, Nonfood Compound, Nonprocessing Area Product, General

Directions

1. Shake well before using. 2. Check the product on a small inconspicuous area of the surface to be de-waxed to make sure there is no attack. Do not spray on painted or varnished surfaces. Wipe off any overspray immediately. 3. Turn can UPSIDE DOWN and hold 6-10 inches from baseboard or surface to be sprayed. A thin even coating should cover the wax. 4. Wait 3 to 5 minutes, longer in case of substantial build-up. Wet scrub the surface with an abrasive pad or scrub brush. Repeat until all wax is removed. 5. Rinse surface with clean water and allow area to dry thoroughly before re-polishing.